

					Stck. Qty.	Art.-Nr. Zubehör Art.-No. Accessories
	Stck. Qty.	Art.-Nr. Art.-No. für Isomat 3/5	Art.-Nr. Art.-No. für Isomat 4	Bestückungsfolge (v. innen nach außen) Assembly sequence (inside to outside)	R1	6 283316 (19.5 mm)
					R2	6 296565 (4.8 mm)
A1	1	282615 B	282615 B	R1/R2/A1		
A2	1	282615 B	282615 B	R1/R2/A2		
A3	1	282616 B	282615 B	R1/R2/A3		
A4	1	282616 B	282615 B	R1/R2/A4		
F1	1	282617 B		R1/R2/F1		
F2	1	282617 B		R1/R2/F2		
		Zulässige Abweichung Permissible tolerance		Oberflächenabwicklung Circumference		VP PU
				mech. polished		-
				umf. total		
Paßmaße Close tol.		Abmaße Std. tolerance		beschichtet coated		Maßstab Scale 1 : 1
Original / Änderung Revision / Version 0201				Datum Date		
Name Finkemeyer				14.09.2006		finkca
Ring 283316 hinzugefügt		gez. drawn		Finkemeyer		
		gepr. checked		Winkler		
		ges. seen		Nienhäuser		
		SCHÜCO				Benennung Title
		Zeichn.-Nr. Drawing No.				393450 RP 1000
		EDV erstellt Ohne Unterschrift gültig generated by EDP valid without signature				Ersatz für Replacement for