

					Stck. Qty.	Art.-Nr. Zubehör Art.-No. Accessories
	Stck. Qty.	Art.-Nr. Art.-No. für Isomat 3/5	Art.-Nr. Art.-No. für Isomat 4	Bestückungsfolge (v. innen nach außen) Assembly sequence (inside to outside)	R1	6 296449 (2.0 mm)
					R2	6 296210 (10.0 mm)
A1	1	283920	283920	R1/R2/A1		
A2	1	283920	283920	R1/R2/A2		
A3	1	283921	283920	R1/R2/A3		
A4	1	283921	283920	R1/R2/A4		
F1	1	283922		R1/R2/F1		
F2	1	283922		R1/R2/F2		
		Zulässige Abweichung Permissible tolerance		Oberflächenabwicklung Circumference		VP PU
				mech. polished		Info-Plan:
				uml. total		
Paßmaße Close tol.				beschichtet coated		
Original / Änderung Revision / Version		0302		Datum Date		Werkstoff Material
Name		28.10.2014		Name		
Serienbez. korrigiert		gez. drawn		Finkemeyer		
		gepr. checked		Winkler		
		ges. seen		Nienhüser		Schüco AWS 90 BS.SI+
						
		Zeichn.-Nr. Drawing No.				442320 RP 1000
		EDV erstellt Ohne Unterschrift gültig generated by EDP valid without signature				
		Ersatz für Replacement for				