

					Stck. Qty.	Art.-Nr. Zubehör Art.-No. Accessories
	Stck. Qty.	Art.-Nr. Art.-No. für Isomat 3/5	Art.-Nr. Art.-No. für Isomat 4	Bestückungsfolge (v. innen nach außen) Assembly sequence (inside to outside)	R1	6 296449 (2.0 mm)
					R2	6 296210 (10.0 mm)
A1	1	283920	283920	R1/R2/A1		
A2	1	283920	283920	R1/R2/A2		
A3	1	283921	283920	R1/R2/A3		
A4	1	283921	283920	R1/R2/A4		
F1	1	283922		R1/R2/F1		
F2	1	283922		R1/R2/F2		

		Zulässige Abweichung Permissible tolerance		Oberflächenabwicklung Circumference		VP PU	Info-Plan:	
				mech. polished		-		
				uml. total				
Paßmaße Close tol.				Abmaße Std. tolerance		beschichtet coated		- - -
Original / Änderung Revision / Version 0100				Datum Date		Name		Werkstoff Material
Name				05.03.2015				
				gez. drawn		Winkler		
				gepr. checked		Finkemeyer		
				ges. seen		Nienhüser		Schüco AWS 90.SI+
								
				Zeichn.-Nr. Drawing No. 480370 RP 1000				
				EDV erstellt Ohne Unterschrift gültig generated by EDP valid without signature		Ersatz für Replacement for		